

Experts in lightability[™]

BEKARAY BEKASTAR


Decorative LED post top range



BEKASTAR



Wall bracket version





Key advantages

- Designed and manufactured in South Africa
- Corrosion resistant
- Available in a battery back-up version
- Integral removable control gear
- Robust top cover
- Available in various colours
- Available in a wall bracket version
- 47W version performs equally to 100W HPS or 125W MV version
- LED Retrofit Kit available for existing installations
- Provides energy savings of up to 70%
- · Low maintenance requirements
- Effective high-power LED, 4000K at a colour rendering index >70
- 5-year warranty (Terms and conditions apply)

Characteristics

GENERAL INFORMATION

Testing standard	SANS 475, SANS 60598, SANS 62262			
Housing	BEKARAY: Top cover - Glass-filled nylon	BEKASTAR: Top cover - Die-cast	aluminium	All: Spigot base - High- pressure die-cast aluminium
Diffuser	High-impact acrylic			
Housing finish	BEKARAY: Telegrey (RAL 7045), Textured f	BEKASTAR: Textured finish Black (RAL 9017), Textu		Textured finish
Aerodynamic resistance (CxS)	BEKARAY: 0.14m ²	BEKARAY: 0.14m ² BEKASTAR: 0.24m ²		1 ²
Standard mounting	Bottom-entry Ø76mm			
Spigot length	≥ 80mm			
Nominal voltage	198-264V – 50Hz			
Surge protection	10kV / 10kA			
Operating temperature range (Ta)	-20°C up to +35°C			
	BEKARAY			BEKASTAR
Wattage (up to)	47W		47W	
Nominal flux (up to)	7,917lm		7,917lm	
Luminaire output flux (up to)	6,967lm		6,967lm	
Luminaire efficacy (up to)	154lm/W			154lm/W
Colour temperature	4000K (Neutral white 740) CRI ≥70			
Lifetime of the LEDs @Tq 25°C	100,000h - L90B10			
Lifetime of the Driver @Tg 25°C	100,000h ≤10% failure rate			













IAI

Please consult your sales representative for more information.

SPORT AREA









www.beka-schreder.co.za

Designed and manufactured by BEKA Schréder (Pty) Ltd

2024-04



Copyright © BEKA Schréder (Pty) Ltd – 13 West View Road – Olifantsfontein (South Africa) • The information, descriptions and illustrations herein are of only an indicative nature. Due to advanced developments, we may be required to alter the characteristics of our products without notice. As these may present different characteristics according to the requirements of individual countries, we invite you to consult us.