


LEDBAY

LED lowbay and highbay




LED-BAY-MIDI



LED-BAY-MAXI 1



LED-BAY-MAXI 2



CONTROL



CIRCLE LIGHT



For project details



LOCALLY
manufactured



IP 66

Up to
IK 10

10kV
optional



Key advantages


- Designed and manufactured in South Africa
- Highly efficient and energy saving (replaces up to 1000W HID light sources)
- Very flexible: Available for lowbay or highbay applications
- Suitable for Food & Beverage industry with polycarbonate protector option
- Optimised heatsink design by means of vertical ribs for heat dissipation for up to 177W for the LEDBAY-MIDI, and up to 475W for the LEDBAY-MAXI
- Designed to operate LED light sources in an ambient temperature (Tq) environment of at least 25°C, without reducing the useful lifetime of up to 100 000 hours
- Long lifetime and low maintenance, no lamp replacement for more than 10 years
- Various optical solutions available
- Suitable for very low Unified Glare Rating (UGR) requirements
- Flicker-free lighting
- Optional motion sensor for even higher energy savings (MIDI only)
- Available in a battery back-up version (MIDI only)
- Available in Zone 2 and 21/22 versions (excludes LEDBAY-MAXI 2 version)
- 5-year warranty (Terms and conditions apply)

Characteristics

GENERAL INFORMATION

Testing standard	SANS 60598, SANS 62262	
Housing	Marine grade high-pressure die-cast aluminium (EN 1706 AC-44300)	
Protector	High-impact clear glass	High-impact polycarbonate (optional)
Housing finish	MIDI: Pearl Light Grey (RAL 9022), Textured finish	MAXI: Unpainted
Standard mounting	MIDI: Eyebolt for suspension chain	MAXI: U-bracket
Nominal voltage	198-264V – 50Hz	
Surge protection	MIDI: 10kV / 10kA (optional)	MAXI: 10kV / 10kA 20kV / 20kA (optional)
Operating temperature range (Ta)	MIDI: -30°C up to +35°C	MAXI: -30°C up to +45°C

LEDBAY	MIDI	MAXI 1	MAXI 2
Wattage (up to)	177W	315W	475W
Nominal flux (up to)	29,485lm	53,566lm	85,185lm
Luminaire output flux (up to)	26,537lm	45,531lm	72,407lm
Luminaire efficacy (up to)	150lm/W	145lm/W	156lm/W
Colour temperature	4000K (Neutral white 740) CRI ≥70		
Lifetime of the LEDs @Tq 25°C	MIDI: 100,000h - L70B10	MAXI: 100,000h - L95B10	
Lifetime of the Driver @Tq 25°C	100,000h ≤10% failure rate		



BEKA Schröder

Experts in lightability™

SABS
ISO 9001



www.beka-schreder.co.za

Designed and manufactured by BEKA Schröder (Pty) Ltd



LOCALLY
manufactured

2024-04

Copyright © BEKA Schröder (Pty) Ltd – 13 West View Road – Olifantsfontein (South Africa) • The information, descriptions and illustrations herein are of only an indicative nature. Due to advanced developments, we may be required to alter the characteristics of our products without notice. As these may present different characteristics according to the requirements of individual countries, we invite you to consult us.