

SOL-ONE MINI

Integrated solar luminaire

SA PAT. 2012/07685



Bottom entry version



Side entry version



Key advantages

- Designed and manufactured in South Africa
- Flexible LED engine configurations to cover a wide range of applications
- Spigot options are available for both bottom and side-entry installation
- Optional remote management functionality enables efficient seasonal scheduling adjustments, reducing on-site intervention and optimizing operational performance
- Low glare and aesthetic visual appearance
- Designed to operate from sunset to sunrise using dimming profiles and movement sensors where applicable
- It has sufficient autonomy to operate reliably at night for up to two consecutive overcast or rainy days
- Specifically engineered for all geographical locations in Africa
- Hail- and corrosion-resistant solar module
- Circular economy 3-star rating
- Warranty up to 5 years (Terms and conditions apply)

Characteristics

GENERAL INFORMATION

Autonomy days	2 days
Geographical location	Designed and optimised for various locations
Aerodynamic resistance (CxS)	0.36m ²
Solar module technology / Rated lifetime	Monocrystalline photovoltaic module: 25 years / 80%
Energy storage technology / Expected lifetime	Lithium: 5-8 years
System operating voltage	12V DC
Operating temperature range (Ta)	-10°C up to +40°C

SOL-ONE MINI

Nominal flux (up to)	7,685lm
Nominal efficacy (up to)	258lm/W
Colour temperature	4000K (Neutral white 740), 3000K (Warm white 730), 5700K (Cool white 757) CRI ≥70
Lifetime of the LEDs @Tq 25°C	100,000h - L95B10



OFF-GRID AREAS




URBAN &
RESIDENTIAL
STREETS



BIKE &
PEDESTRIAN
PATHS



SQUARES &
PEDESTRIAN
AREAS



CAR PARKS



SHOPPING
CENTRES



SECURITY
LIGHTING



SPORT AREAS

BEKA Schröder

Experts in lightability™

SABS
ISO 9001



www.beka-schreder.co.za

Designed and manufactured by BEKA Schröder (Pty) Ltd



LOCALLY
manufactured

2025-09

Copyright © BEKA Schröder (Pty) Ltd – 13 West View Road – Olifantsfontein (South Africa) • The information, descriptions and illustrations herein are of only an indicative nature. Due to advanced developments, we may be required to alter the characteristics of our products without notice. As these may present different characteristics according to the requirements of individual countries, we invite you to consult us.