

OMNISTAR

ECO

LED floodlighting solution



For project details



LOCALLY
manufactured



SABS
APPROVED

IP 66

Up to
IK 10

10kV



CONTROL



CIRCLE
LIGHT



Key advantages

- Designed and manufactured in South Africa
- Designed to operate LED light sources of 195W in an ambient temperature (T_a) environment of up to 25°C, without reducing the useful lifetime of 100 000 hours, at a lumen depreciation of not more than 10% (L90B10)
- Cost effective and efficient lighting solution to maximise energy and maintenance cost savings in highmast applications
- Instant switch on/off
- Sports applications: ball impact resistant
- Maintenance free
- Surge protection: Standard driver with additional 10kV/10kA
- Circular economy 3-star rating
- 3-year warranty (Terms and conditions apply)

Characteristics

GENERAL INFORMATION

Testing standard	SANS 60598, SANS 62262, SANS 475	
Housing	Marine grade high-pressure die-cast aluminium (EN 1706 AC-44300)	
Protector	High-impact clear glass	High-impact polycarbonate (optional)
Housing finish	Unpainted aluminium	
Aerodynamic resistance (CxS)	0.0773m ² (calculated at a 60° rake angle)	
Standard mounting	Stirrup enabling adjustable inclination on-site	U-bracket (optional)
Nominal voltage	198-264V – 50Hz	
Surge protection	10kV / 10kA	
Operating temperature range (T _a)	-40°C up to +45°C	


OMNISTAR

ECO

Wattage	195W
Nominal flux	30,238lm
Luminaire output flux	27,244lm
Luminaire efficacy	140lm/W
Colour temperature	4000K (Neutral white 740); 5700K (Cool white 757) CRI ≥70
Lifetime of the LEDs @T _q 25°C	100,000h - L90B10
Lifetime of the Driver @T _q 25°C	100,000h ≤10% failure rate



INTERCHANGE



AREA



INDUSTRIAL HARBOUR



HIGHMAST LIGHTING



FAÇADE



SIGNAGE



STADIUM



UNIVERSITY TRACK & FIELD

Case Study: 400W HPS Comparison



Luminaire fitted with
400W
High Pressure Sodium
lamp

OMNISTAR-ECO
195W

Energy Savings

400W
HPS/T

OMNISTAR-
ECO 195W

100%

55%
Energy
Savings^(*)

45%

432W

195W

	Luminaire fitted with 400W High Pressure Sodium lamp	OMNISTAR-ECO 195W
Luminaire power consumption (W)	432	195
9 x luminaires per mast (per mast total) (W)	3888	1755
Total power per mast (kWh)	3.89	1.76
Total power saved per mast (kWh)	-	2.13
Total power saved per mast (%)	-	55

Detail on lighting design comparison available on request.



Kuruman, South Africa

BEKA Schröder

Experts in lightability™

SABS
ISO 9001



www.beka-schreder.co.za

Designed and manufactured by BEKA Schröder (Pty) Ltd



LOCALLY
manufactured

2024-04

Copyright © BEKA Schröder (Pty) Ltd – 13 West View Road – Olifantsfontein (South Africa) • The information, descriptions and illustrations herein are of only an indicative nature. Due to advanced developments, we may be required to alter the characteristics of our products without notice. As these may present different characteristics according to the requirements of individual countries, we invite you to consult us.