

BEKABRITE

LED bollard



Key advantages

- Designed and manufactured in South Africa
- Robust and vandal resistant
- Head sealed from pole base
- Corrosion-resistant poles
- Marine grade high-pressure die-cast aluminium head (EN 1706 AC-44300)
- Available in various colours
- 3-year warranty (Terms and conditions apply)

Characteristics

GENERAL INFORMATION

Testing standard	SANS 60598, SANS 62262	
Head	Marine grade high-pressure die-cast aluminium head (EN 1706 AC-44300)	
Pole	Buried: Glass filament wound GRP	Surface mount: Extruded aluminium (optional)
Protector	High-impact clear acrylic	
Housing finish	Various options available. Please consult your sales representative for more information.	
Mounting	Buried	Surface mount (optional)
Nominal voltage	198V-277V - 50Hz	
Operating temperature range (Ta)	-20°C up to +35°C	

BEKABRITE


Wattage	20W
Nominal flux	2,676lm
Nominal efficacy	134lm/W
Colour temperature	4000K (Neutral white 840) CRI ≥80
Lifetime of the LEDs @Tq 25°C	80,000h - L70
Lifetime of the Driver @Tq 25°C	100,000h ≤10% failure rate



BIKE & PEDESTRIAN PATH



SQUARES & PEDESTRIAN AREA



CAR PARK



SHOPPING CENTRE



PUBLIC BUILDINGS



SPORT AREA



SERVICE STATION

BEKA Schröder

Experts in lightability™

SABS
ISO 9001



www.beka-schreder.co.za

Designed and manufactured by BEKA Schröder (Pty) Ltd



LOCALLY
manufactured

2025-01

Copyright © BEKA Schröder (Pty) Ltd – 13 West View Road – Olifantsfontein (South Africa) • The information, descriptions and illustrations herein are of only an indicative nature. Due to advanced developments, we may be required to alter the characteristics of our products without notice. As these may present different characteristics according to the requirements of individual countries, we invite you to consult us.