

Experts in lightability™





## ROUGHGUARD

Vandal-resistant linear LED luminaire




1ft version - opal diffuser



2ft version - opal diffuser



2ft version - clear diffuser



## Key advantages

- · Designed and manufactured in South Africa
- · Vandal proof
- · Available in two sizes for applications flexibility
- · Available in a battery back-up version
- Designed to operate LED light sources of up to 52W in an ambient temperature (Tq) environment of up to 35°C, without reducing the useful lifetime of up to 50 000 hours, at a lumen depreciation of not more than 30% (L70B10)
- · Corrosion-resistant high-pressure die-cast aluminium body
- · One-piece injection-moulded clear polycarbonate diffuser
- Removable gear tray for ease of maintenance
- 3-year warranty (Terms and conditions apply)

## Characteristics

## GENERAL INFORMATION

Testing standard	SANS 60598, SANS 62262	
Housing	Marine grade high-pressure die-cast aluminium (EN 1706 AC-44300)	
Diffuser	Polycarbonate	
Housing finish	Pearl Light Grey (RAL 9022), Textured finish	
Standard mounting	Drill positions or bracket mounting	
Nominal voltage	198-277V – 50Hz	
Surge protection	10kV / 10kA	
Operating temperature range (Ta)	Standard version: -35°C up to +40°C	Battery back-up version: -35°C up to +40°C

ROUGHGUARD	1ft	2ft
Wattage (up to)	15W	52W
Nominal flux (up to)	2,050lm	8,447lm
Luminaire output flux (up to)	1,635lm	7,349lm
Luminaire efficacy (up to)	109lm/W	143lm/W
Colour temperature	4000K (Neutral white 840) CRI ≥80	
Lifetime of the LEDs @Tq 25°C	50,000h - L70B10	
Lifetime of the Driver @Tq 25°C	90,000h ≤10% failure rate	





















SECURITY LIGHTING

PUBLIC BUILDINGS

MANUFACTURING

LOADING BAY

HAULAGE LIGHTING

**BEKA**Schréder











www.beka-schreder.co.za

Designed and manufactured by BEKA Schréder (Pty) Ltd

