

SABS



SOL-ONE

MAXI

Integrated solar luminaire





Key advantages

- · Designed and manufactured in South Africa
- Flexible LED engine configurations to cover a wide range of road and highmast lighting applications
- · Fixed spigot base plug-and-play design, eliminating installation errors
- · Low glare
- · Aesthetic visual appearance
- Designed to operate from sunset to sunrise using dimming profiles and movement sensors where applicable
- It has sufficient autonomy to operate reliably at night for up to two consecutive overcast or rainy days
- · Specifically engineered for all geographical locations in Africa
- · Hail- and corrosion-resistant solar module
- · Circular economy 3-star rating
- Warranty up to 5 years (Terms and conditions apply)

Characteristics

GENERAL INFORMATION

Autonomy days	2 days
Geographical location	Designed and optimised for various locations
Aerodynamic resistance (CxS)	0.63m²
Solar module technology / Rated lifetime	Monocrystalline photovoltaic module: 25 years / 80%
Energy storage technology / Expected lifetime	Lithium: 5-8 years
System operating voltage	12V DC
Operating temperature range (Ta)	-10°C up to +40°C

SOL-ONE MAXI

Nominal flux (up to)	18,424lm
Nominal efficacy (up to)	241lm/W
Colour temperature	4000K (Neutral white 740), 3000K (Warm white 730), 5700K (Cool white 757) CRI $\geq\!70$
Lifetime of the LEDs @Tq 25°C	100,000h - L95B10





















SQUARES & PEDESTRIAN

SHOPPIN

SECURITY LIGHTING

SPORT AREAS

HIGHMAST











www.beka-schreder.co.za

Designed and manufactured by BEKA Schréder (Pty) Ltd

