

# LED BEAM

Linear LED spotlight & wallwasher



For project details



**LOCALLY**  
manufactured



IP 66

Up to  
IK 10



CONTROL

**DMX**



Food & Beverage

# Key advantages

- Designed and manufactured in South Africa
- Designed to operate LED light sources of up to 72W in an ambient temperature (Ta) environment of up to 40°C, without reducing the useful lifetime of 100 000 hours, at a lumen depreciation of not more than 30% (L70B10)
- Available in module lengths of: 330mm/630mm/930mm/1230mm and 1830mm
- Fully dimmable 0%-100%
- CRI for white light  $\geq 70$
- Designed for ambient temperature rating (Ta) of 40°C
- Available in different beam distributions
- Corrosion-resistant design
- Available with many accessories
- Supplied with 3m cable
- 3-year warranty (Terms and conditions apply)

## Characteristics

### GENERAL INFORMATION

Testing standard	SANS 60598
Body	Aluminium extrusion
End-caps	Die-cast aluminium (6063T6)
Protector	PMMA
Nominal voltage	24V DC
Operating temperature range (Ta)	-20°C up to +40°C

### LEDBEAM

Wattage (up to)	72W
Nominal flux (up to)	9,450lm
Luminaire output flux (up to)	6,615lm
Luminaire efficacy (up to)	131lm/W
Colour temperature	5000K (Neutral white 750) CRI $\geq 70$
Lifetime of the LEDs @Tq 25°C	100,000h - L70B10



FAÇADE



SIGNAGE



BRIDGE



HAULAGE  
LIGHTING



ASSEMBLY LINE

# BEKA Schröder

Experts in lightability™

**SABS**  
ISO 9001



[www.beka-schreder.co.za](http://www.beka-schreder.co.za)

Designed and manufactured by BEKA Schröder (Pty) Ltd



**LOCALLY**  
manufactured

2026-01

Copyright © BEKA Schröder (Pty) Ltd - Twenty One Industrial Estate - 10 Purlin Street North - Olifantsfontein (South Africa) • The information, descriptions and illustrations herein are of only an indicative nature. Due to advanced developments, we may be required to alter the characteristics of our products without notice. As these may present different characteristics according to the requirements of individual countries, we invite you to consult us.