

**BEKA Schréder**

Experts in lightability™

**SABS**

ISO 9001

**SABS**

ISO 14001

# LEDDUO

Decorative wall mounted LED luminaire



Round



Square



For project details



LOCALLY  
manufactured



IP 65

IK 07



# Key advantages

- Designed and manufactured in South Africa
- Designed to operate LED light sources of up to 2\*7W in an ambient temperature environment of up to 35°C, without reducing the useful lifetime of 50 000 hours, at a lumen depreciation of not more than 30% (L70)
- Medium and wide beam distributions
- Ingress protection - IP 65
- 3-year warranty (Terms and conditions apply)

## Characteristics

### GENERAL INFORMATION

Testing standard	SANS 60598, SANS 62262
Body	Marine grade aluminium (EN 1706 AC-44300)
Protector	High-impact clear glass
Housing finish	Pearl Light Grey (RAL 9022), Textured finish
Nominal voltage	198-264V – 50Hz
Operating temperature range (Ta)	-20°C up to +35°C

### LEDDUO

Wattage (up to)	14W
Nominal flux (up to)	2*988lm
Luminaire output flux (up to)	2*889lm
Luminaire efficacy (up to)	127lm/W
Colour temperature	4000K (Neutral white 840); 3000K (Warm white 830) CRI ≥80
Lifetime of the LEDs @Tq 25°C	50,000h - L70B10
Lifetime of the Driver @Tq 25°C	100,000h ≤10% failure rate



FAÇADES



SHOPPING CENTRES



PUBLIC BUILDINGS



COMMERCIAL BUILDINGS



BRIDGES

# BEKA Schréder

Experts in lightability™

**SABS**  
ISO 9001

f in X YouTube

[www.beka-schreder.co.za](http://www.beka-schreder.co.za)

Designed and manufactured by BEKA Schréder (Pty) Ltd

2026-01

Copyright © BEKA Schréder (Pty) Ltd - Twenty One Industrial Estate - 10 Purlin Street North - Olifantsfontein (South Africa) • The information, descriptions and illustrations herein are of only an indicative nature. Due to advanced developments, we may be required to alter the characteristics of our products without notice. As these may present different characteristics according to the requirements of individual countries, we invite you to consult us.

 **LOCALLY**  
manufactured